ONSET

S-CIA-CM14

12-bit 4-20mA Input Adapter Sensor

The 12-bit 4-20 mA Input Adapter interfaces with any sensor providing a 4-20 mA signal to connect to smart sensor compatible HOBO stations. This adapter features both a non-switched input and a battery-saving switched input that extends the life of external batteries. It also provides a trigger signal for controlling power to attached external sensors, while offering digital filtering which improves measurement accuracy with 32 readings/sample and 60 Hz noise rejection.



Key Advantages:

- 12-bit resolution
- Digital filtering improves measurement accuracy with 32 readings/sample—4-20 mA adapter has 60 Hz noise rejection
- Measurement averaging over logging interval further enhances accuracy
- Plug-in modular connector for easy interface with HOBO® stations
- · Screw terminal for connecting to sensors
- HOBO RX3000 and U30 stations have room for two adapters
- Use with HOBO USB Micro Station and HOBO MicroRX Station requires Smart Sensor Consolidator Box (S-ADAPT-6) and an extension cable.
- · Represents one data input channel

HOBO S-CIA-CM14 Sensor Specifications

Measurement range: 4-20 mA (measures down to 0 mA to detect error condition)

Operating temperature range: -40° to 75°C (-40° to 167°F)

Accuracy: ±40 µA ±0.3% of reading (over operating temperature range)

Resolution: ±4.93 µA

Input impedance: 124 ohms (differential input)

Sensor trigger source: Voltage: 2.5 V ±2.4%; maximum current: 1 mA

Warm-up time: 300 ms ±3% (fixed)

Measurement time: 16.6 ms ±3% to filter out 60 Hz noise

Cable length: 14 cm (5.5 inch)

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- ► Email sales@onsetcomp.com
- Call 1-508-759-9500
- In U.S. toll free 1-800-564-4377
- Fax 1-508-759-9100

Technical Support (8am to 6pm ET, Monday through Friday)

- ► Contact Product Support www.onsetcomp.com/support/contact
- Call 1-508-759-9500
- In U.S. toll free 1-877-564-4377

Onset Computer Corporation 470 MacArthur Boulevard Bourne, MA 02532