



## HOBO<sup>®</sup> UX100-003 Data Logger

Temperature/Relative Humidity 3.5%

The HOBO UX100-003 Temperature/Relative Humidity data logger records temperature and relative humidity (within 3.5% accuracy) in indoor environments with its integrated sensors. The data logger is ideal for monitoring occupant comfort in office buildings, tracking food storage conditions in warehouses, logging temperature trends in server rooms, and measuring humidity levels in museums.



### Key Advantages:

- Easy-to view LCD display
- Large memory capacity
- Visual high & low alarm thresholds
- New Burst and Statistics logging modes
- User-replaceable Relative Humidity sensor
- Compatible with HOBOWare and HOBOWare Pro software for logger setup, graphing and analysis

## HOBO UX100-003 Data Logger Specifications

### Temperature Sensor

---

**Range:** -20° to 70°C (-4° to 158°F)

**Accuracy:** ±0.21°C from 0° to 50°C (±0.38°F from 32° to 122°F)

**Resolution:** 0.024°C at 25°C (0.04°F at 77°F)

**Response time:** 4 minutes in air moving 1 m/s (2.2 mph)

**Drift:** <0.1°C (0.18°F) per year

### RH Sensor

---

**Range:** 15% to 95% (non-condensing)

**Accuracy:**

±3.5% from 25% to 85% including hysteresis at 25°C (77°F); below 25% and above 85% ±5% typical

**Resolution:** 0.07% at 25°C (77°F) and 30% RH

**Response time:** 43 seconds to 90% in airflow of 1 m/s (2.2 mph)

**Drift:** <1% per year typical

### Logger

---

#### Logger Operating Range

**Logging:** -20° to 70°C (-4° to 158°F); 0 to 95% RH (non-condensing)

**Launch/readout:** 0° to 50°C (32° to 122°F) per USB specification

**Logging rate:** 1 second to 18 hours, 12 minutes, 15 seconds

**Logging modes:** Normal, Burst or Statistics

**Memory modes:** Wrap when Full or Stop when Full

**Start modes:** Immediately, Push Button, Date & Time or Next Interval

**Stop modes:** When Memory Full, Push Button, or Date & Time

**Restart mode:** Push Button

**Time accuracy:** ±1 minute per month at 25°C (77°F)

**Battery life:** 1 year, typical with logging rate of 1 minute and sampling interval of 15 seconds or greater

**Battery type:** One 3V CR2032 lithium battery

**Memory:** 128 KB (84,650 measurements, maximum)

**Download type:** USB 2.0 interface


**Full memory download time:** 20 seconds

**LCD:** LCD is visible from: 0° to 50°C (32° to 122°F); the LCD may react slowly or go blank in temperatures outside this range

**Size:** 3.66 x 8.48 x 1.52 cm (1.44 x 3.34 x 0.6 in.)

**Weight:** 30 g (1.06 oz)

**Environmental rating:** IP50

 - The CE Marking identifies this product as complying with all relevant directives in the European Union (EU)

## Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- ▶ Email [sales@onsetcomp.com](mailto:sales@onsetcomp.com)
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-800-564-4377
- ▶ Fax 1-508-759-9100

Technical Support (8am to 6pm ET, Monday through Friday)

- ▶ Contact Product Support [www.onsetcomp.com/support/contact](http://www.onsetcomp.com/support/contact)
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-877-564-4377

Onset Computer Corporation  
470 MacArthur Boulevard  
Bourne, MA 02532