



**The Ultimate Fresh & Salt Water Analyzer
for Aquariums and Aquaculture applications**



Up to 8 Tests in 2 Minutes!

Ready to go anywhere!



WaterLink® SpinTouch® FX

“Every now and then a technology emerges that changes people’s lives. For people who test water, that time is now.”
— David LaMotte, President


Available Tests:

Alkalinity
Ammonia
Calcium
Hardness
Magnesium
Nitrate
Nitrite
pH
Phosphate

Up to 8 tests in 2 Minutes!

- Reliable Results
- Super Fast & Simple
- Auto-Record Keeping
- Rugged and Portable

The innovative **WaterLink® Spin Touch® FX** photometer does all your fresh and salt water testing for you. Each sealed reagent disk contains the precise amount of reagent needed to run a complete series of tests.—both fresh and salt water disks are available. Just fill one unique Spin reagent disk with less than 3 mL of water and all your vital tests are done automatically—in just 2 minutes! It’s the most advanced system for wet chemistry methods ever produced. Now analysts can achieve test results without time consuming test and clean-up procedures. This ground-breaking analysis system is so simple anyone can use it! No vials to fill, no prep time, no guessing!



So Simple! So Fast!

*“Proven analytical chemistry has combined with **Centrifugal Fluidics Photometry** to create the breakthrough WaterLink® Spin Touch®”*



Centrifugal Fluidics Photometry™

The Device *Precise analysis of up to 8 parameters in 2 minutes!*



6-Wavelength
Colorimeter

Bluetooth



Touchscreen




Portable



Pre-Measured,
Sample-Injected,
Reagent
Cartridge
Disks



Order Code 3589



Reliable Results

- Virtually Eliminates User-Error
- Pre-Measured Reagents
- Exact Reaction Time and Auto-Blanking
- Meter Calibration Check System
- 6-Wavelength Photometer

Super Fast & Simple

- 2 Minutes for up to 8 Complete Tests Using One Disk
- Fill Disk and Insert > Tap "Start Test" > Read Results

Data Logging

- Stores Test Dates, Times, Results, and Location
- Download via USB to PC

Stand-Alone or Cloud-Connected

- Touchscreen Operation
- Connect to WaterLink Solutions via Bluetooth®

Rugged and Portable

- Innovative Water-Resistant Housing
- Internal, Rechargeable Batteries

Bluetooth® is a registered trademark of Bluetooth® SIG, Inc.

Instrument Type:	Centrifugal Fluidics Photometer
6 Wavelengths:	390 nm, 428 nm, 470 nm, 525 nm, 568 nm, 635 nm
Display:	Color Capacitive Touchscreen, 3.5", 320 X 240 pixel resolution
Languages	English, French, Spanish, German, Italian, Portuguese, Dutch, Swedish, Turkish, Chinese
Batteries:	Lithium Ion, Rechargeable (Full Charge in 10-12 hours), 150 tests per charge
Communication:	Bluetooth, USB-C
Calibration:	Factory Set, Field Calibration via Internet Connection
Data Storage:	Last 250 Test Results with Date, Time, Location
Water Resistance:	Rubber Co-molded Base, Rubber USB Port Plug, Gasketed Display & Hinge
Size & Weight:	22.6 L x 12.7 W x 11.4 H cm; 0.79 kg; 8.5 L x 4.9 W x 4.1 H inches; 1.74 lb
Operation:	Single On/Off/Reset Button with Indicator Light, Touchscreen
Firmware:	Internet Updateable (New Tests, New Test Calibrations, etc.)
Printer:	Optional Bluetooth® Printer [Code 5-0066]; 384 dots per line at 8 dots/mm resolution
Certification	CE

The Complete Lab

WaterLink® Spin Touch® FX Order Code 3589

Includes: Photometer, Instruction Manual, Quick-Start Instructions, 3 Syringes, Meter Check Disk, Disk Cover, Sample Bottle, USB Cable with AC Adapter, Carrying Case [Disks sold separately]



The Reagent Cartridge Disks

Disks come individually packaged in foil pouches in boxed packs of 50.



FX Fresh Water Disk 50/box Order Code 4353-H

Test Parameter	Range
Alkalinity	0-250 ppm
Ammonia NH ₃	0-4.0 ppm
Hardness	0-500 ppm
Nitrate NO ₃	0-300 ppm
Nitrite NO ₂	0-2.0 ppm
pH	4.5-10.0 pH
Phosphate PO ₄	0-2.0 ppm

Disk Patent No. 8,734,734
 FCI Patent No. 8,987,000
 TCI Patent No. 8,993,337
 FCI EU Patent No. EP2784503 A1

FX Salt Water Disk 50/box Order Code 4354-H

Test Parameter	Range
Alkalinity	0-300 ppm
Ammonia NH ₃	0-4.0 ppm
Calcium	200-800 ppm
Magnesium	500-2200 ppm
Nitrate NO ₃	0-60 ppm
Nitrite NO ₂	0-2.0 ppm
pH	6.5-10.0 pH
Phosphate PO ₄	0-2.0 ppm

Disk Patent No. 8,734,734
 FCI Patent No. 8,987,000
 TCI Patent No. 8,993,337
 FCI EU Patent No. EP2784503 A1

The Optional Software

WaterLink Solutions™

- Cloud-based and **Free**
- Instantly capture date, time, test results, and location for each pond or tank
- View in real time water quality test results of each pond or tank
- Monitoring Dashboard* provides alerts and complete water quality history of each pond or tank
- Powerful, customizable treatment engine
- Download free iOS or Android WaterLink® Solutions App for your mobile device
- Sign up for your WaterLink Solutions account at www.softwarecenter.lamotte.com

*Monitoring Dashboard at nominal monthly charge



802 Washington Ave | Chestertown, Maryland 21620 USA
 Tel: 800-344-3100 or 410-778-3100
 Email: info@lamotte.com
waterlinkspintouch.com | lamotte.com